


PARTS ENCLOSED: HARDWARE INCLUDED:

- | | |
|------------------------|--------------------------------|
| (A) Mounting plate (1) | a. Green ground screw (1) |
| (B) Back plate (1) | b. Plastic wire connectors (2) |
| | c. Plate Screws (2) |
| | d. Mounting screws (2) |



IMPORTANT SAFETY INSTRUCTIONS

WE RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.

This fixture has been rated for up to two (2) 60-watt maximum Type B candelabra bulbs.

To avoid the risk of fire, do not exceed the recommended wattage.

WARNINGS:

All wires are connected. When unpacking, be careful not to pull wires as a bad connection may result. Do not connect electricity until your lamp is fully assembled. To reduce the risk of fire, electrical shock, or personal injury, always turn off lamp and allow it to cool prior to replacing lightbulb.

Do not touch bulb when fixture is turned on or look directly at lit bulb.

Keep flammable materials away from lit bulb.

⚠ WARNING: This product can expose you to lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

THIS IS NOT A TOY AND THE PRODUCT HAS NO PLAY VALUE.

ASSEMBLY & INSTALLATION

- Carefully remove all parts from the box and remove all plastic covering.
- Turn OFF power to the junction box where the lamp will be installed.
- Pull the electrical cord of "J BOX" through the exit hole of the mounting plate (A).
- Attach the ground wire from the fixture to the ground junction box wire from the outlet box (Usually green or bare wire) with a plastic wire connector (b) and wrap the connection with electrical tape. Screw the green ground screw (a) into the mounting plate (A), and wrap the bare ground wire around the ground screw.
- Connect the hot wire to the hot junction box wire (usually black) with a plastic wire connector (b) and wrap the connection with electrical tape. Connect the neutral wire to the neutral junction box wire (usually white) with a plastic wire connector (b) and wrap the connection with electrical tape.
- Attach the mounting plate (A) to the outlet box using the mounting screws (d). Tighten with a screwdriver.
- Attach the back plate (B) to the mounting plate (A) using the enclosed plate screws (c). Tighten screws with a screwdriver.
- Insert two 60-watt Type B bulbs into threaded sockets.
- Place two clip shades (not included) onto the bulbs.
- Restore power to the junction box and test lamp fixture.
- Installation is complete.

CARE INSTRUCTIONS

Do not use polishes or cleaners on your lamp. JUST WIPE CLEAN WITH SOFT CLOTH.