


RH

CHAMPEAUX CANTILEVER FLOOR LAMP

PARTS ENCLOSED

- (A) Lamp Pole (1)
- (B) Lamp Base (1)
- (C) Washers (2)
- (D) Bolts (1)
- (E) Allen Wrench (1)
- (F) Felt Sheet (1)
- (G) Shade (1)
- (H) Bulb (1)
- (I) Shade Cover (1)
- (J) Lamp Arm (1)



CHAMPEAUX CANTILEVER FLOOR LAMP

IMPORTANT SAFETY INSTRUCTIONS

INSTALLATION BY A LICENSED ELECTRICIAN IS STRONGLY RECOMMENDED.

For safety purposes, this lamp is equipped with a polarized plug (one blade is wider than the other). If the plug does not fit securely into outlet, do not force it - contact a professional electrician. Use the plug with an extension cord only if it can be fully inserted into the cord's socket. Never alter the plug in any way.

This fixture has been rated for one (1) 6-Watt maximum Type PAR 16 LED bulb (H) (included). To avoid the risk of fire, do not exceed the recommended wattage.

WARNINGS

All wires are connected. When unpacking, be careful not to pull wires, as a bad connection may result. Do not connect electricity until your fixture is fully assembled. To reduce the risk of fire, electrical shock, or personal injury, always turn off fixture and allow it to cool prior to replacing the light bulb. Do not touch or look directly at the bulb when fixture is illuminated. Keep flammable materials away from lit bulb.



WARNING: This product can expose you to lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

THIS IS NOT A TOY AND THE PRODUCT HAS NO PLAY VALUE.



WARNING: STRANGULATION HAZARD

Keep cord at least 3 ft away from cribs, bassinets, and toddler beds.
Keep out of reach of children under 3.

ASSEMBLY & INSTALLATION

SHUT OFF THE MAIN ELECTRICAL SUPPLY FROM THE FUSE BOX OR CIRCUIT BREAKER PANEL.

1. Carefully remove all parts from the box and remove all plastic covering.
2. Join Lamp Pole (A) and Lamp Base (B) together by aligning the holes and secure with Washers (C) and Bolts (D). Tighten with Wrench (E).
3. Pull the wire from exit hole until tight.
4. Remove backing sheet from Felt Sheet (F). Affix Felt (F) to the bottom of Lamp Base (B).
5. Insert Bulb (H) into the socket.
6. Thread Shade Cover (I) to the bottom of Shade (G).
7. Plug into proper electrical outlet and test fixture.
8. Assembly is complete.

TO ADJUST HEIGHT

Adjust Lamp Shade (G) by Swing Lamp Arm (J) to desired angle.

CARE INSTRUCTIONS

Do not use polishes or cleaners on your lamp. Just wipe clean with a soft cloth.