

# RESTORATION HARDWARE


Thank you for purchasing Restoration Hardware Lighting. Our assortment is crafted with the highest quality details in mind and each collection is clad in one of our signature finish options. Each item's surface is sealed which eliminates the need for polishing and ensures the lasting brilliance of your piece for years to come.

## PARTS ENCLOSED: HARDWARE INCLUDED:

- |                         |                                |
|-------------------------|--------------------------------|
| (A) Mounting plate (1)  | (a) Green ground screw (1)     |
| (B) Canopy (1)          | (b) Plastic wire connector (2) |
| (C) Weighted pulley (1) | (c) Plate screw (2)            |
| (D) Handle (1)          | (d) Mounting screw (2)         |
| (E) Shade (1)           | (e) Metal ring (4)             |

## BURNHAM PULLEY PENDANT

### Direct Wire Installation



## IMPORTANT SAFETY INSTRUCTIONS:

WE RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.  
This fixture has been rated for up to (1) 60-watt maximum TYPE A STANDARD bulb.  
To avoid the risk of fire, do not exceed the recommended wattage.

## WARNINGS:

All wires are connected. When unpacking, be careful not to pull wires as a bad connection may result. Do not connect electricity until your lamp is fully assembled.

To reduce the risk of fire, electrical shock, or personal injury, always turn off lamp and allow it to cool prior to replacing light bulb.

Do not touch bulb when fixture is turned on or look directly at lit bulb.

Keep flammable materials away from lit bulb.

## TO ASSEMBLE:

1. Carefully remove all parts from the box and remove all plastic covering.
2. Turn OFF power to the junction box where the lamp will be installed.
3. Attach the ground wire from the fixture to the ground junction box wire from the outlet box (Usually green or bare wire) . Screw the green ground screws(a) into the mounting plate(A).
4. Connect the hot wire to the hot junction box wire (usually black) with a plastic wire connectors(b) and wrap the connection with electrical tape. Connect the neutral wire to the neutral junction box wire (usually white) with a plastic wire connector(b) and wrap the connection with electrical tape.
5. Attach the mounting plate to the outlet box using the mounting screws(d). Tighten with a screwdriver.
6. Attach the canopy(B) to the mounting plate using the enclosed plate screws(c). Tighten screws with the screwdriver.
7. Place glass shade(E) onto the socket, then, insert handle(D) to cover the socket and screw metal ring(e) to thread into it.
8. Insert a 60 watt Type A bulb(not include) into threaded socket.
9. Pull the handle adjust the lamp head up and down, and locate the lamp head in desired height.
10. Restore power to the junction box and test lamp fixture.
11. Installation is complete.

## CARE INSTRUCTIONS:

Do not use polishes or cleaners on your lamp.

JUST WIPE CLEAN WITH SOFT CLOTH.