

FT-120 Andalusia Fountain

Professional installation is recommended for this fountain!



Pump Kit Parts List

PK300 pump (1)
LED-LIGHT (1)
LED-TRANS (1)
#5 wing nut drain stopper (1)
#7 wing nut drain stopper (1)
Approx. 20" length of 1/2" Black non-kink tubing (1) **
Approx. 2" length of 5/8" clear vinyl tubing (1) **
Approx. 2" length of 1/2" CPVC pipe (1)
Approx 42" length of 3/8" rebar (2)
10oz tube of silicone (1)
Hose clamps (1) *
Wedges (2)

* Hose clamps may be used as flow restrictors

**Black non-kink tubing and clear vinyl tubing have been preassembled

***Do not preassemble the LED Light and Transformer

FOUNTAIN INFORMATION:

This fountain holds approximately 60 gallon of water.

This fountain does not fit under a Campania fountain cover.

Compatible with #10 Refill Device and LED Kits
(No stoppers are required to use the refill kit or LED kit for this fountain.)

TOOLS REQUIRED:

Bubble Level



Caulking Gun



Hammer



PUMP INFORMATION:
OEMPF320 - 320 GPH Pump
16 FT cord length

- WINTER CARE -

Fountain bowls/tops and other fountain components, which collect water, should not be left outside in the winter since any component, which fills with water and freezes may crack. Likewise components such as pedestals, which remain in a basin, filled with water, which then freezes, may also crack or crumble. Ideally, therefore, a fountain should always be stored indoors or in a dry protected place such as a covered porch away from the elements. However, if a fountain must be left outside:

- (1) Remove pump, rubber stoppers, drainpipes, finials, and other small components for storage indoors. Note that stoppers or drainpipes are removed to allow drainage in the event water accumulates in any basin.
- (2) Raise fountain base from ground with wood strips so that base will not freeze to the ground surface.
- (3) Cover or wrap the fountain with burlap or other absorbent material (old blanket or towel) and then cover securely with plastic, making sure that water will not accumulate in the basin or other fountain component and freeze;
- (4) Check fountain periodically to insure that plastic is secure and water is not accumulating in any fountain component.

- GENERAL FOUNTAIN TIPS -

Install fountains on a level surface. You will need a properly grounded 110-volt (AC only) GFCI protected receptacle near the fountain for your pump. All pumps are submersible and must be completely underwater to function properly. Test all pumps and adjust to full output prior to assembly. It is not recommended that fountains be placed directly on grass or dirt. Position the channel opening at the base of each fountain toward the electrical outlet to be used since the pump cord will be threaded through this opening.

Check out YouTube for a "How to" video.

For more Campania product information visit www.campaniainternational.com

All of our cast stone is proudly




Made in USA


FT-120 Andalusia Fountain

Professional installation is recommended for this fountain!


Assemble your fountain on a level surface capable of holding a minimum of 2200 pounds with approximately a 13.5 square foot footprint.




FT-120C (1080 lbs)
56.25"L x 30"W x 17.5"H



FT-120A (532 lbs)
55"L x 16"W x 38"H



(2) FT-120CAP (>1 lb)
1"L x 1"W x 1"H



FT-120B (37 lbs)
13"L x 7.5"W x 15.25"H

1. Place the base (FT-120C) into position where the fountain will be installed, ensuring that it is level.
2. Using a caulking gun, run a bead of silicone along the top of the basin (FT-120C) where the water feature (FT-120A) will be placed. Take care not to use too much silicone to minimize oozing of silicone from between the pieces.
3. Place the water feature (FT-120A) on top of the basin (FT-120C) making sure that the PVC pipe holes are lined up between the top of the basin and the bottom of the water feature.
4. **BE CAREFUL NOT TO PINCH FINGERS WHEN LOWERING!**
 - a. **Hand holds have been molded into the water feature for easier assembly.**
5. Clean off any excess silicone with your finger or a dry rag as quickly as possible.
6. Using a hammer, gently tap the 2" length of CPVC pipe into the PVC coupling in the bottom of the water feature (FT-120A).
 - a. **Note: To prevent breakage, do not do this step early.**
7. Place the #5 drain stopper into the hole at the bottom of the bowl on the water feature (FT-120A).
8. Drop the rebar support pipes into the holes at the top of the water feature (FT-120A).
 - a. Check that the pipes have dropped all the way through the water feature (FT-120A) AND basin (FT-120C) before going forward.
9. Insert the stone caps (FT-120CAP) into the holes over the pipes.
 - a. Note: The caps are removable.
10. Assemble the pump kit
 - a. Using a hose clamp, attach the 1/2" black tubing to the pump outlet.
11. Place the pump and LED light in the fountain and feed the cords through the hole between the basin (FT-120C) and water feature (FT-120A).
 - a. Attach the LED light to the transformer outside of the fountain.
12. Fit the other piece of 5/8" clear tubing over the CPVC installed into the water feature (FT-120A) in step 6.
13. Place the pump cover (FT-120B) over the pump along the back of the basin.
14. Place the #7 drain stopper into the hole at the bottom front of the basin.
15. Place LED light in the front of the basin aiming the light at the waterfall.
16. Let the fountain sit 24 hours before filling it with water.