


Step 1


Remove all packaging from inside and outside of the umbrella.

Step 2


Pull the pin to unlock the cam lock handle. Open the cam lock handle.

**Step 3**


Once you have leveled the stem using the base installation instructions, slide the beauty cover and umbrella over the security stem as illustrated below (security stem is included with umbrella).

**Step 4**

Push cam lock handle down until it is locked into the security stem. Insert the pin into the lock handle.

**Step 5**

Gently separate each rib individually from the center hub approximately 10 inches. If the rib does not move easily, do not force. Inspect the product for additional packaging.



Step 1

Connect the umbrella cable swedge eye to the cable bracket on top of the bottom trolley cart using the provided security pin (**figure a**).

Note: If the cable does not have enough give to reach the bracket (see step 2), pull the black rope until the cable swedge eye reaches the cable bracket on top of the bottom trolley.

Step 2

Set the mast lock in the open/up position (**figure b**).

Step 3


Insert the crank handle and turn clockwise to open the umbrella (**figure c**).

You will know the umbrella is fully opened/engaged when the auto-scope meets the mast (**figure d**).

Note: your umbrella may or may not come with high-wind stabilizers (**figure e**).

Step 4

Once fully open set the mast lock in the down/locked position and remove the crank handle when not in use (**figure f**).



WITH LED LIGHT (IF APPLICABLE)**Step 1**



Connect the electrical cord to the outlet.

Step 2

Tap plate once to power on-off, or touch and hold for light dimming control.

LIGHTING SPECIFICATIONS

Power Supply:	
Input Voltage	90 - 305 VAC
Input Current	0.6A / 115 VAC 0.3A / 230 VAC
Output Voltage	12 VDC
Output Power	40 Watts



When not in use, the canopy should be carefully folded and secured with the tie-strap.

Note:
close umbrella during wind conditions that exceed manufacturer's specifications.

care & maintenance

[terms & conditions]



Frames

TUUCI frames are constructed from durable and weather resistant materials, including anodized aluminum, Durateak, fiberglass and marine quality hardwood. All fasteners (nuts, bolts, pulleys, cam cleats, etc.) are stainless steel and will withstand the most difficult environments. However, proper care and maintenance is important to extend the useful life of the product. TUUCI products used on ocean front properties, or other salty environments, should be regularly washed with fresh water to limit oxidation.

Prior to opening, ensure that the shade product is properly secured to its shade anchor, using the locking system intended for the specific product (star knob, hitch pin or cam lock). **WHEN OPENING A TUUCI PARASOL, GENTLY SEPARATE EACH RIB 4" TO 6" FROM THE CENTER POST, BEFORE RAISING THE HUB.** Do not force hub if it does not rise easily. When closing the parasol, pull the fabric out from between the struts to avoid pinching and tearing the fabric.

TUUCI frames have been tested for structural integrity in winds exceeding 50 miles per hour, and are very durable. However, these tests were performed with special, extremely secure shade anchors; caution and common sense must be applied in extreme winds and weather. TUUCI generally recommends that its shade products be closed in any weather that is uncomfortable for the people using the products, and is directly related to the size, weight and security of the shade anchor. Please use reasonable and cautious judgment when determining when the parasol should be closed.

Canopies

TUUCI's parasol canopies are normally made with Sunbrella® fabric, and should be cared for as described below (for fabric other than Sunbrella®, refer to manufacturer). Sunbrella® fabric should be cleaned regularly before dirt is allowed to accumulate and become embedded in the fabric. The fabric canopy can be cleaned without being removed from the frame. Simply brush off any loose dirt or particles; hose down and clean with a mild soap in lukewarm water (no more than 100F.) Rinse thoroughly to remove soap. Allow fabric to air dry. **DO NOT USE DETERGENTS!**

For stubborn stains clean with TUUCI Fabric Cleaner TM. Scrub vigorously with a soft bristle brush, sponge, or clean towel. Allow fabric to air dry. This method of cleaning may remove part of the water repellency. If water repellency is a factor, the fabric should receive an application of an air-curing water repellent treatment (such as TUUCI Fabric Shield TM).

Sunbrella® may be machine washed but a water repellent treatment must be applied to the fabric after washing to reestablish water repellency. Sunbrella® is made from 100% acrylic fiber and is thermoplastic or heat sensitive. When washing or cleaning, **DO NOT SUBJECT TO EXCESSIVE HEAT** as the fabric will shrink. **DO NOT STEAM PRESS OR DRY IN ELECTRIC OR GAS DRYERS**, but allow air to dry.

In cases where the parasol is taken down and stored during the winter season, the Sunbrella® canopy should be cleaned, allowed to air dry, and stored in a dry, well ventilated area. A TUUCI Protective Cover should be used when umbrella is not in use.

Shade Anchors

ALWAYS BE SURE THAT PARASOL CENTER POLE IS FIRMLY ATTACHED TO BASE BEFORE OPENING PARASOL. Clean above ground parasol bases regularly to maintain appearance. To clean, gently wash with soap and water using a non-abrasive cloth or pad. Check three bolts in base plate regularly to ensure that they remain fully tightened. Inspect weekly if parasol bases are moved on a regular basis.

Do not roll ACF (Aluminum Shell, Concrete Filled) bases on their side as damage to shell or finish can occur. Touch up bases with exterior paint as needed. Touch up can be ordered from the TUUCI parts department. Wheeled parasol bases are intended for use on even surfaces. Move bases slowly and with caution on uneven surfaces. Do not use on stairways or over distances, which exceed 50 feet, as damage to welded wheel tray will occur.