


RESTORATION HARDWARE

Thank you for purchasing Restoration Hardware Lighting. Our assortment is crafted with the highest quality details in mind and each collection is clad in one of our signature finish options. Each item's surface is sealed which eliminates the need for polishing and ensures the lasting brilliance of your piece for years to come.

PARTS ENCLOSED:

- (A) BACKPLATE
- (B) MOUNTING PLATE
- (C) BACKPLATE SCREW (X3)
- (D) MOUNTING SCREW (X2)
- (E) WIRE NUT (X3)

OUTDOOR FILAMENT SCNCE



IMPORTANT SAFETY INSTRUCTIONS:

- * These instructions are provided for your safety. It is very important that they are read completely before beginning the installation of your fixture.
- * **DIRECT WIRE FIXTURES: WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.**
- * This fixture has been rated for up to (1) 100W MAX. Type A bulb.
- * To avoid risk of fire, do not exceed the recommended wattage.

WARNING:

- * Switch power to fixture off before replacing the bulb, making sure the fixture and the bulb have had sufficient time to cool down.
- * Do not subject lamp to any shock while lit as shattering of bulbs can occur.

TO ASSEMBLE:

1. SHUT OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/ CIRCUIT BREAKER.
2. Remove fixture and all parts from carton. Do not throw away any parts.
3. Remove all packing material from fixture.
4. Remove mounting plate (B) from backplate (A) by removing screws (C). Set screws (C) aside.
5. Carefully pull the wiring from wall outlet box. Thread the wires through the center hole in mounting plate (B).
6. Affix mounting plate (B) to wall outlet box with mounting screws (D) provided.
7. Make proper electrical connections described in steps 8 - 10. A LICENSED ELECTRICIAN IS RECOMMENDED.
8. Connect ground (green or silver in color) wire from fixture to ground wire in the outlet box. Fasten wires together with wire nut (E) and tightly wrap the connection with electrical tape.
9. Attach hot wire from fixture (black in color or smooth side of wire) to hot wire from outlet box. Fasten wires together with wire nut (E) and tightly wrap connection with electrical tape.
10. Attach neutral wire from fixture (white in color or ribbed side of wire) to neutral wire from outlet box. Fasten wires together with wire nut (E) and tightly wrap connection with electrical tape.
11. Slide backplate (A) over mounting plate (B). Thread screws (C) into vacant holes at the top and bottom of backplate (A) to secure the fixture to the mounting surface.
12. Install one (1) 40W MAX. Type A, medium base filament bulb (INCLUDED) into socket.
13. Reconnect main electrical supply from the fuse box/circuit breaker and test fixture.

CARE INSTRUCTIONS:

To clean, use a soft cloth. DO NOT use any chemical or abrasive cleaners.