


RESTORATION HARDWARE

ODEON SCONCE

PARTS ENCLOSED

ITEMS	DIAGRAM	DESCRIPTION	QTY.
(A)		Mounting Screws (Not included)	4 sets
(B)		Body	1
(C)		Wire Nut	3
(D)		Glass Drop	20
(E)		Bulb+Spare	3+1

IMPORTANT SAFETY INSTRUCTIONS:

1. Use an authorized and certified electrician for consultation and installation.
2. This fixture has been rated for 3 x 15-watt maximum E12 standard incandescent bulb.
3. To avoid the risk of fire, do not exceed the recommended wattage.
4. The wall must have at least the capacity of 5 times the weight of the wall lamp.
For this light at least a wall capacity of 37.75kg(83.20lb) is required.
5. The manufacturer and distributor accepts no liability for incorrect installation.
6. For indoor use only.
7. Keep away from children.

Warnings:

1. Turn off/unplug and allow to cool before replacing bulb (lamp).
2. Bulb (lamp) gets HOT quickly! Only contact switch/plug when turning on.
3. Do not touch hot lens, guard, or enclosure.
4. Do not remain in light if skin feels warm.
5. Do not look directly at lighted lamp.
6. Keep lamp away from materials that may burn.
7. Do not touch the bulb (lamp) at any time. Use a soft cloth. Oil from skin may damage bulb (lamp).

PRODUCT DESCRIPTION:

General material: Iron
Height: 39.0 cm (15.35in)
Width: 16.5 cm (6.50in)
Length: 33.5cm (13.19in)
Weight:7.55 kg(16.64lb)
Hardwired

TO ASSEMBLE:

1. Carefully remove all parts from the box and remove all plastic covering.
2. Turn OFF power to the junction box where the wall lamp will be installed.
3. Loosen screw cap (B2) and (B3) from body (B) and detach bracket (B1).
4. Loosen bolts(B5) from body (B) and detach metal ring (B4).
5. Attach bracket (B1) to the wall with mounting screws (A).
6. Connect the ground wire from the fixture to the ground junction box wire (Usually the green or bare wire) and wrap the connection with electrical tape. Connect the hot wire to the hot junction box wire (Usually black or smooth) with a plastic wire nut (C) and wrap the connection with electrical tape. Connect the neutral wire to the neutral junction box wire (Usually white or ribbed) with a plastic wire nut (C) and wrap the connection with electrical tape.
7. Attach body (B) to bracket (B1) with screw caps (B2) and (B3).
8. Fasten the bulbs (E) to the lampholders.
9. Hang the glass drops (D) from bottom layer to top layer and keep flat surface of glass drop inside. To ensure safety of chandelier during glass drop installation, please maintain level of chandelier by ensuring you install glass drops in balanced way on opposite ends of light.
10. Attach the metal ring (B4) to body (B) with screws (B5).
11. Restore power to the junction box and test wall lamp fixture.

CARE INSTRUCTIONS:

1. Make sure that the power is turned off and bulb has cooled before handling.
2. Wipe clean with a dry cloth / mild soapy solution. Do not use corrosive cleaners.
3. The cable/cord of this wall lamp cannot be replaced: If the cable is damaged, do not use the lamp.

ENVIRONMENT:

Special waste handling may be required. Please contact your local authorities for more information.

