






RESTORATION HARDWARE

HARLOW CRYSTAL TRIPLE SCONCE

PARTS ENCLOSED

ITEMS	DIAGRAM	DESCRIPTION	QTY.
(A)		Mounting Screws (Not included)	10sets
(B)		Body	1
(C)		Wire Nut	3
(D)		Bulb	3+1
(E)		Glass Block	3

IMPORTANT SAFETY INSTRUCTIONS:

1. Use an authorized and certified electrician for consultation and installation.
2. This fixture has been rated for 3 x 40-watt maximum E12 T6 standard bulb.
3. To avoid the risk of fire, do not exceed the recommended wattage.
4. The wall must have at least the capacity of 5 times the weight of the wall lamp.  
For this light at least a wall capacity of 58.1kg (128.08lb) is required.
5. The manufacturer and distributor accepts no liability for incorrect installation.
6. For indoor use only.
7. Keep away from children.

Warnings:

1. Turn off/unplug and allow to cool before replacing bulb (lamp).
2. Bulb (lamp) gets HOT quickly! Only contact switch/plug when turning on.
3. Do not touch hot lens, guard, or enclosure.
4. Do not remain in light if skin feels warm.
5. Do not look directly at lighted lamp.
6. Keep lamp away from materials that may burn.
7. Do not touch the bulb (lamp) at any time. Use a soft cloth. Oil from skin may damage bulb (lamp).

PRODUCT DESCRIPTION:

General material: Iron  
Height: 79.1 cm (31.14in)  
Width: 15.0 cm (5.91in)  
Length: 14.0 cm (5.51in)  
Weight: 11.62 kg (25.62lb)  
Hardwired

TO ASSEMBLE:

1. Carefully remove all parts from the box and remove all plastic covering.
2. Turn OFF power to the junction box where the wall lamp will be installed.
3. Loosen the bolts (B2) (B5)and remove the top slot (B3) (B4) (B6) from body (B).
- 4.Put glass block (E) onto the bottom slot (B7) of the body. Put the top slot (B3) (B4) (B6) onto glass block (E) and re-attach top slot (B3) to body (B) with bolts (B2) (B5).
5. Loosen bolts (B8) (B9)from body (B) and detach bracket (B1).
6. Attach bracket (B1) to the wall with mounting screws (A).
7. Connect the ground wire from the fixture to the ground junction box wire (Usually the green or bare wire) and wrap the connection with electrical tape. Connect the hot wire to the hot junction box wire (Usually black or smooth) with a plastic wire nut (C) and wrap the connection with electrical tape. Connect the neutral wire to the neutral junction box wire (Usually white or ribbed) with a plastic wire nut (C) and wrap the connection with electrical tape.
8. Attach body (B) to bracket (B1) with bolts (B8)(B9).
9. Fasten the bulb (D) to the lampholder.
10. Restore power to the junction box and test wall lamp fixture.

CARE INSTRUCTIONS:

1. Make sure that the power is turned off and bulb has cooled before handling.
2. Wipe clean with a dry cloth / mild soapy solution. Do not use corrosive cleaners.
3. The cable/cord of this wall lamp cannot be replaced: If the cable is damaged, do not use the lamp.

ENVIRONMENT:

Special waste handling may be required. Please contact your local authorities for more information.

