

RESTORATION HARDWARE

PERALTA ROUND 36" CHANDELIER

PARTS ENCLOSED: HARDWARE INCLUDED:

- | | |
|------------------------|--------------------------------|
| (A) Fixture stud (1) | (a) Plastic wire connector (7) |
| (B) Swivel (1) | (b) Toggle (4) |
| (C) Canopy (1) | (c) Screw (4) |
| (D) Ring (1) | (d) Allen key (1) |
| (E) Base (1) | |
| (F) Tube (1) | |
| (G) Center box (1) | |
| (H) Extension tube (4) | |
| (I) Rod (3) | |

IMPORTANT SAFETY INSTRUCTIONS:

MAKE SURE THESE ARE INSTALLED BY A PROFESSIONAL OR LICENSED ELECTRICIAN.

WARNINGS:

All wires are connected. When unpacking, be careful not to pull wires as a bad connection may result. Do not connect electricity until your lamp is fully assembled.

Do not touch the LED strip or look directly at lit LED strip.
Keep flammable materials away from lit LED strip.

This lighting fixture contains lead, a chemical known to the State of California to cause cancer, birth defects and other reproductive harm. Wash hands after installing, handling, cleaning or otherwise touching this light fixture.

TO ASSEMBLE:

1. Carefully remove all parts from the box and remove all plastic covering.
2. Shut off electrical supply at main fuse box / circuit breaker. A licensed electrician should install this fixture.
3. Insert Rods (I) into the fixture and turn clockwise until tight.
4. Put the Tube (F) onto the Center box (G) and turn clockwise until the Tube (F) screw into the Center box (G). Secure the Tube (F) by using Allen key (d) provided.
5. Put the Tube (F) onto the Swivel (B) and turn clockwise until the Tube (F) screw into the Swivel (B). Secure the Tube (F) by using Allen key (d) provided.
6. If need, disassemble the existing suspension tube by unscrewing the sections apart. Pull the wire back through the Swivel section that will need to be extended. Locate the Extension tubes (H) and check the actual suspension length needed to the incremental fixture suspension length to determine number of extensions.
7. Attach Fixture stud (A) to ceiling beam through outlet box. Have a professional contractor reinforce the ceiling.
8. Refer to the wiring diagram provided for accurate wire connections. Cut out the redundant wires after the professional installation. Keep proper ventilation around the driver, and do not stack any object on it.
9. Attach the Canopy (C) with the light fixture to the affixed Fixture stud (A) and secure with the Ring (D).
10. Restore power to the junction box and test lamp fixture.
11. Installation is complete.

CARE INSTRUCTIONS:

Do not use polishes or cleaners on your lamp.
JUST WIPE CLEAN WITH SOFT CLOTH.

