

# RESTORATION HARDWARE

## UNION FILAMENT NARROW SCONCE

### PARTS ENCLOSED

- (A) Metal Anchors (4)
- (B) Mounting Plate (1)
- (C) Wall Screws (4)
- (D) Mounting Screws (2)
- (E) Base Screws (4)
- (F) Fixture Base (1)
- (G) Thumbscrew (1)
- (H) Lantern Box (1)
- (J) Socket (1)
- (K) Light Bulb(1)

### IMPORTANT SAFETY INSTRUCTIONS:

WE RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.  
This fixture has been rated for up to one (1) 60-watt maximum Type A bulb (included). To avoid the risk of fire, do not exceed the recommended wattage.

### WARNINGS:

1. Do not remove the lamp from its packaging by pulling on the power cord, as a bad connection may result.
2. Do not connect electricity until your lamp is fully assembled.
3. To reduce the risk of fire, electrical shock, or personal injury, always turn off lamp and allow it to cool prior to replacing light bulb.
4. Do not touch bulb when fixture is turned on or look directly at lit bulb.
5. Keep flammable materials away from lit bulb.

### TO ASSEMBLE:

1. SHUT OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER!
2. Carefully remove all parts from the box and remove all metal covering.
3. Remove mounting plate (B) from the fixture base (F) by unscrewing base screws (E).
4. Place mounting plate (B) at desired location on the wall. Mark center points locations for four hang holes with a pencil. Remove mounting plate (B).
5. Drill small holes on each point location on the wall, each hole should be large enough to accommodate the metal anchors (A). Push metal anchors (A) into the holes on the wall.
6. Attach mounting plate (B) to the wall outlet by aligning the holes and secure by inserting wall screws (C) to the metal anchors (A) and mounting screws (D) to the wall outlet box.
7. Attach the fixture ground wire (green) to the ground wire from the outlet box (usually green) with a metal wire connector and wrap the connection with electrical tape.
8. Connect the hot wire (black wire) to the hot outlet box wire (usually black) with a plastic wire connector and wrap the connection with electrical tape.
9. Connect the neutral wire (white wire) to the neutral outlet wire (usually white) with a plastic wire connector and wrap the connection with electrical tape.
10. Attach fixture base (F) to mounting plate (B), tighten with base screws (E).
11. Loosen thumbscrew (G), and open the lantern box (H).
12. Insert light bulb (included) into socket (J).
13. Close the lantern box (H), and secure the thumbscrew (G). (See left illustration)
14. Restore power to outlet box and check operation of fixture.
15. Assembly is complete.

### CARE INSTRUCTIONS:

Wipe all surfaces with a soft dry cloth. Clean glass with a mild soap and water mixture. Do not use any harsh cleaners (including ammonia-based products) or abrasives, as they will damage the finish.

