

# RESTORATION HARDWARE

## INDIAN DYE BASKET PENDANT 14"

### PARTS ENCLOSED:

- (A) Terminal mounting strip
- (A1) Hot wire
- (A2) Neutral wire
- (A3) Ground wire
- (A4) Wire nut
- (B) Canopy mounting screw
- (C) Canopy
- (D) Dye basket pendant
- (E) Bulb - 40W - 1 piece
- (F) Latch - to lock the door of Pendant


### IMPORTANT SAFETY INSTRUCTIONS:

- These instructions are provided for your safety. It is very important that they are read carefully before beginning the installation of your fixture.
- For your safety, it is strongly recommended, that two people hang the lighting fixture.
- Turn off electricity at the main circuit breaker panel before beginning installation.
- This direct wire fixture must be installed by a certified and licensed electrician. Customer should not attempt to install.
- This fixture has been rated up to maximum 40W bulb for medium base.
- To avoid the risk of fire, do not exceed the recommended wattage.
- If any special control devices are used with this fixture, follow the instructions carefully to assure full compliance with N.E.C. Requirement.
- If there are any questions, contact a licensed electrical contractor.

### WARNINGS:

- To reduce the risk of fire, electrical shock or personal injury, always turn off light fixture and allow it to cool prior to replacing light bulb.
- Do not touch bulb when fixture is on. Do not look directly at lit bulb.
- Keep flammable material away from lit bulb.

### TO ASSEMBLE:

1. Shut off electrical supply at main fuse box/circuit breaker. A licensed electrician should install this fixture.
  2. Unpack all the parts and keep on a soft surface.
  3. Unscrew Canopy mounting screw (B). Remove Terminal mounting strip (A).
  4. Attach Terminal mounting plate (A) with attachment screws (not provided) to Outlet box.
  5. Pull wires from ceiling outlet box and proper electrical connections described in step 6 - 8. In step 6 - 8 fasten proper wires together with Wire nut (A4) as shown on the picture below and tightly wrap connections with electrical tape (not provided).
- 
6. Attach the Ground wire from (A3) fixture to Ground wire from Outlet box. Fasten wire together with Wire Nut (A4) and tightly wrap connection with electrical tape (not provided).
  7. Attach Hot wire (A1) from fixture to Hot wire from Outlet box. Fasten wires together with Wire Nut (A4) and tightly wrap the connection with electrical tape (not provided).
  8. Attach Neutral wire (A2) from fixture to neutral wire from Outlet box and tightly wrap the connection with electrical tape (not provided).
  9. Fix the Pendant (D) to Terminal mounting strip (A) Slide up the Canopy and fix it by tightening the Canopy mounting screw (B).
  10. Slide up the Latch (F) and open the door of the Pendant (D).
  11. Insert Bulb (E) into socket and close the door and push the Latch (F) downward to lock the Pendant (D).
  12. Restore power to the ceiling outlet box and test fixture.
  13. Assembly is complete.

**CARE INSTRUCTIONS:** To clean, use a soft cloth only. Do not use any chemical or abrasive cleaners.

