

RESTORATION HARDWARE

Thank you for purchasing Restoration Hardware Lighting. Our assortment is crafted with the highest quality details in mind and each collection is clad in one of our signature finish options. Each item's surface is sealed which eliminates the need for polishing and ensures the lasting brilliance of your piece for years to come.

PARTS ENCLOSED :

- (A) CORD GRIP
- (B) CROSS BAR WITH GROUNDING SCREW
- (C) CEILING ROSE
- (D) RETAINING NUT
- (E) CEILING LOOP
- (F) HOOK (attached to Metal Chain)
- (G) METAL CHAIN
- (H) POWER CORD
- (I) GROUND WIRE
- (J) HOOK (attached to metal Chain)
- (K) LOOP IN PENDANT
- (L) PENDANT

IMPORTANT SAFETY INSTRUCTIONS :

* These instructions are provide for your safety. It is very important that they are properly read **completely** before beginning the installation of your fixture.

DIRECT WIRE FIXTURE.

WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.

WARNINGS :

Turn off power (unplug from the wall outlet) before replacing the bulb, making sure, The bulb had sufficient time to cool down. DO NOT subject the lamp to any shock while lit as shattering of lamp may result.

19TH C. French Empire Chainmail Chandelier 14'

TO ASSEMBLE :

1. SHUT OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX / CIRCUIT BREAKER
2. Remove all parts from carton. Do not throw away any parts.
3. Check if the grommets have been inserted in components **Cross bar (B)** and **Ceiling Loop (E)**. If not insert this yourself.
4. Un-screw the **Cross Bar (B)** from the **Ceiling Loop (E)**. Affix the **Cross Bar (B)** directly to the **Junction Box** using screws provided.
5. **To place the Lamps in the sockets please slide the chains and place four, Type CA lamps in the four sockets and then re-arrange the chains back to their place.**
6. Open the wire coil- **Power Cord (H)** and the **Ground Wire (I)** coming out from the **Pendant (L)** and lay them together and parallel to each other.
7. Attach the **Hook (J)** on one side of the chain to the **Pendant Loop (K)** in the **Pendant (L)**
8. Weave the wires **Power Cord (H)** and the **Ground Wire (I)** through the **Metal Chain (G)** -taking the wires through alternate links of the **Metal Chain (G)**.
9. Lift carefully the **Pendant (L)** with one end of the **Metal Chain (G)** attached to it and place it in one elevated position (eg on a step ladder) in such a way that the wire cords can freely reach the ceiling Junction Box.
10. Guide the wires- coming out from the **Pendant (L)** and running woven through the **Metal Chain (G)** - through the **Ceiling Loop (E)**, **Retaining Nut (D)** and the **Ceiling Rose (C)** in the order mentioned.
11. Further guide the wires through the **Threaded Tube** of the **Cross Bar (B)**.
12. Now you can see the wire coming out from the **Cross Bar(B)**
13. **MAKE PROPER ELECTRICAL CONNECTIONS. THIS INSTALLATION SHOULD BE DONE BY A QUALIFIED LICENSED ELECTRICIAN. ELECTRICAL CONNECTIONS SHALL BE MADE LIVE TO LIVE AND NEUTRAL TO NEUTRAL.**
14. Connect the Grounding Wire (silver colour un-laminated wire) from the **Pendant (L)** to the **Grounding Bolt (painted Green Colour)** attached to the **Cross Bar (B)**
15. Fasten wires together with a plastic Wire Connector (not provided) as follows :- Connect the Neutral Wire of the **Pendant (L)** to the Neutral Wire in the outlet box through the Wire Connector. Connect the Live Wire of the **Pendant (L)** to the Live Wire in the outlet box through the Wire Connector. Tightly wrap Wire Connector with the electrical insulation tape.
16. Slide the **Ceiling Rose (C)** and place it over the **Cross Bar (B)**. Screw the **Ceiling Loop (E)** along with the **Retaining Nut (D)** to the Threaded Pipe of **Cross Bar (B)**. Now screw the **Retaining Nut (D)** upwards so that the **Ceiling Rose (C)** is in contact with the ceiling.
17. Attach the **Hook (F)** of the **Metal Chain (G)** to the **Ceiling Loop (E)**
18. Check weather the connection is sufficiently strong by manually loading the **Metal Chain (G)**.
19. Carefully lower the **Pendant (L)** along with the **Metal Chain (G)** until the **Metal Chain (G)** is taut. Straighten the **Metal Chain (G)** links.

CARE INSTRUCTIONS :

To clean, use a soft cloth only, DO NOT use any chemical or abrasive cleaners.

